

CODE: RP2001
NAME: LIMESTONE ASH
SIZE:24X24



2CM PORCELAIN PAVERS

TECHNICAL SPECIFICATIONS		REFERENCE STANDARD			REQUIRED VALUE		DECLARED VALUE
	DIMENSIONS	ISO 10545-2			COMPLIANT		COMPLIANT
	WATER ABSORPTION	ISO 10545-3			≤ 0,5 %		COMPLIANT
	BREAKING STRENGTH	ISO 10545-4			R ≥35 N/MM² S ≥1300 N		COMPLIANT
	ABRASION RESISTANCE	ISO 10545-7			PEI ONLY FOR GLAZED TILES		
	LINEAR THERMAL EXPANSION	ISO 10545-8			≤ 9x10 ⁻⁵ °C ⁻¹		COMPLIANT
	THERMAL SHOCK RESISTANCE	ISO 10545-9			RESISTANT		RESISTANT
	FROST RESISTANCE	ISO 10545-12			RESISTANT		RESISTANT
	ACID AND ALKALI RESISTANCE	ISO 10545-13			CLASS GB MIN.		LOW CONCENTRATION GLA HIGH CONCENTRATION GHA
	CHEMICAL RESISTANCE	ISO 10545-13			CLASS GB MIN.		GA
	STAIN RESISTANCE	ISO 10545-14			CLASS 3 MIN.		5
	FRICTION COEFFICIENT (SLIPPERINESS)	BCR - ITALIA DM DEL 14-06-89			ASTM - USA ASTM C1028		DIN - GERMANIA DIN 51130
		DRY RUBBER 0,62	WET RUBBER 0,51	DRY LEATHER 0,62	DRY 0,69	WET 0,62	R11
THE PRODUCTS HAVING AN ABSORPTION < 0,5% ARE CLASSIFIED ACCORDING THE UNI CEN STANDARDS “FULLY VITRIFIED TILES” AND ACCORDING TO THE ASTM STANDARDS “IMPERVIOUS TILES”							

WEIGHT AND PACKAGING

Sizes			pcs. x box	sf. x box	lbs. x box	box x pal.	sf. x pal.	lbs. x pal.	
24"X24" 2CM (Rectified)	3/4"	20 mm	2	7.96	71.65	30	238.9	2171	32"x48"x30"
16"X48" 2CM (Rectified)	3/4"	20 mm	3	15.82	138.8	14	221.5	1958	32"x48"x30"