










CODE: RP2025
NAME: CAEMENTUM GRISEO




2CM PORCELAIN PAVERS

SIZE:36X36

TECHNICAL SPECIFICATIONS		REFERENCE STANDARD			REQUIRED VALUE		DECLARED VALUE	
	DIMENSIONS	ISO 10545-2			COMPLIANT		COMPLIANT	
	WATER ABSORPTION	ISO 10545-3			≤ 0,5 %		COMPLIANT	
	BREAKING STRENGTH	ISO 10545-4			R ≥ 35 N/MM ² S ≥ 1300 N		COMPLIANT	
	ABRASION RESISTANCE	ISO 10545-7			PEI ONLY FOR GLAZED TILES			
	LINEAR THERMAL EXPANSION	ISO 10545-8			= < 9x10 ⁻⁵ °C ⁻¹		COMPLIANT	
	THERMAL SHOCK RESISTANCE	ISO 10545-9			RESISTANT		RESISTANT	
	FROST RESISTANCE	ISO 10545-12			RESISTANT		RESISTANT	
	ACID AND ALKALI RESISTANCE	ISO 10545-13			CLASS GB MIN.		LOW CONCENTRATION GLA HIGH CONCENTRATION GHA	
	CHEMICAL RESISTANCE	ISO 10545-13			CLASS GB MIN.		GA	
	STAIN RESISTANCE	ISO 10545-14			CLASS 3 MIN.		5	
	FRICTION COEFFICIENT (SLIPPERINESS)	BCR - ITALIA DM DEL 14-06-89			ASTM - USA ASTM C1028		DIN - GERMANIA DIN 51130	
		DRY RUBBER 0,62	WET RUBBER 0,51	DRY LEATHER 0,62	DRY 0,69	WET 0,62	R11	

THE PRODUCTS HAVING AN ABSORPTION < 0,5% ARE CLASSIFIED ACCORDING THE UNI CEN STANDARDS "FULLY VITRIFIED TILES" AND ACCORDING TO THE ASTM STANDARDS "IMPERVIOUS TILES"

WEIGHT AND PACKAGING

Sizes			pcs. x box	sf. x box	lbs. x box	box x pal.	sf. x pal.	lbs. x pal.	
24"X24" 2CM (Rectified)	3/4"	20 mm	2	7.96	71.65	30	238.9	2171	32"x48"x30"
16"X48" 2CM (Rectified)	3/4"	20 mm	3	15.82	138.8	14	221.5	1958	32"x48"x30"