












CODE: RP2031
NAME: ULTRA SOLID BLACK




2CM PORCELAIN PAVERS

SIZE:24X24

	TECHNICAL SPECIFICATIONS	REFERENCE STANDARD	REQUIRED VALUE		DECLARED VALUE		
	DIMENSIONS	ISO 10545-2	COMPLIANT		COMPLIANT		
	WATER ABSORPTION	ISO 10545-3	≤ 0,5 %		COMPLIANT		
	BREAKING STRENGTH	ISO 10545-4	R ≥ 35 N/MM ² S ≥ 1300 N		COMPLIANT		
	ABRASION RESISTANCE	ISO 10545-7	PEI ONLY FOR GLAZED TILES				
	LINEAR THERMAL EXPANSION	ISO 10545-8	= < 9x10 ⁻⁵ °C ⁻¹		COMPLIANT		
	THERMAL SHOCK RESISTANCE	ISO 10545-9	RESISTANT		RESISTANT		
	FROST RESISTANCE	ISO 10545-12	RESISTANT		RESISTANT		
	ACID AND ALKALI RESISTANCE	ISO 10545-13	CLASS GB MIN.		LOW CONCENTRATION GLA HIGH CONCENTRATION GHA		
	CHEMICAL RESISTANCE	ISO 10545-13	CLASS GB MIN.		GA		
	STAIN RESISTANCE	ISO 10545-14	CLASS 3 MIN.		5		
	FRICTION COEFFICIENT (SLIPPERINESS)	BCR - ITALIA DM DEL 14-06-89		ASTM - USA ASTM C1028		DIN - GERMANIA DIN 51130	
		DRY RUBBER 0,62	WET RUBBER 0,51	DRY LEATHER 0,62	DRY 0,69	WET 0,62	R11

THE PRODUCTS HAVING AN ABSORPTION < 0,5% ARE CLASSIFIED ACCORDING THE UNI CEN STANDARDS "FULLY VITRIFIED TILES" AND ACCORDING TO THE ASTM STANDARDS "IMPERVIOUS TILES"

WEIGHT AND PACKAGING

Sizes			pcs. x box	sf. x box	lbs. x box	box x pal.	sf. x pal.	lbs. x pal.	
24"X24" 2CM (Rectified)	3/4"	20 mm	2	7.96	71.65	30	238.9	2171	32"x48"x30"
16"X48" 2CM (Rectified)	3/4"	20 mm	3	15.82	138.8	14	221.5	1958	32"x48"x30"